

# Looks Like We Might Need to Do Something about That Old Dam of Ours!

by *Randall J. Passmann*

New York's dams are aging and there are over 5,500 of them. The New York State Department of Conservation (DEC) records indicate that 58 percent of the dams around the state are at least 50 years old and 30 percent are at least 80 years old. A majority of the over 5,500 dams known to the DEC are privately owned, followed by local government, New York State, public utilities, and the federal government, in descending order. Many existing dams were designed and constructed using now superseded standards and practices. The lifespan of a particular dam is often a function of the level of ongoing repair and upkeep effort. Smaller dams, without adequate expenditure for proper repair and maintenance, seem to suffer the most from neglect and deterioration.

DEC regulations separate dams into three hazard classifications: High Hazard (Class C), Intermediate Hazard (Class B), and Low Hazard (Class A). The hazard class is essentially a function of a dam's threat to public safety due to its potential to cause loss of life and downstream damage if it were to fail. The higher the dam's hazard class, the greater the design flood event it needs to safely convey.

The Environmental Conservation Law (ECL) emphasizes that the safety of dams is of paramount importance and it is the dam owner's responsibility to operate and maintain their dam in a safe manner. The ECL gives the DEC regulatory authority over dams in the state. The DEC's Dam Safety Section (DSS) is currently working through the regulatory process for revising New York State's dam safety regulations to clarify what is required of dam owners to routinely inspect and maintain their dams in a safe manner. The revised regulations, when adopted, are expected to prompt owners of deficient dams to either repair their dams or to review other alternatives to address the identified deficiencies. The no-action alternative is increasingly unacceptable due to safety issues and regulatory requirements.

The evaluation of financial alternatives to fund dam repair projects is beyond the scope of this article but can include:

- Selling the dam to a responsible owner capable of addressing any dam safety deficiencies
- Forming a Lake Association or Special Taxing District to fund repair, inspection and maintenance costs

- Partnering with a Non-Government Organization (NGO) to promote fish passage through partial breach of a dam, or fish passage addition
- Installing hydroelectric power generating equipment or repairing an existing system to provide a revenue source

## Experienced Engineers Needed

There are a number of engineering methods to address a dam's spillway capacity and stability deficiencies. Commonly used methods to address these deficiencies include enlarging spillways, tension anchoring, and adding structural mass; however, partially or completely removing a dam can also be a cost-effective solution. The particular method chosen requires careful planning and reevaluation throughout the design process, from the project concept stage to design completion.

From the time when conceptual project approaches are developed, it is important to consider the amount of existing engineering data available for a given dam and the potential effect on project cost. These data can include original design record documents; the results of previously completed engineering site investigations; and hydrologic, hydraulic, and structural evaluations. The investigation and design cost, to demonstrate that the dam meets dam safety criteria, may be substantial. A consultant with specific experience on similar projects can help define the overall project and prepare an accurate total project cost estimate. The life-cycle-cost of different alternatives, using a net present value type analysis, can be used for comparison. As the design progresses, the construction cost estimate can be updated, so there is no big surprise when the work is bid.

## Dam Breaching Options

A partial or full breach of a dam is an approach that is being considered by many dam owners to significantly reduce or eliminate future dam liability. The approach selected must lead to a long-term stable situation. For example, just opening a dam's low-level drain and walking away, often leaves a condition that is prone to blockage by debris, and the dam can unexpectedly begin retaining water again.

*continued on page 16*



*Photo courtesy of NYSDEC*

Example of a dam before and after a partial breach project: the remaining low-level drain outlet is discernable along the right edge of each photo.



*Photo courtesy of NYSDEC*

ENVIRONMENTAL CONSULTANTS

METCALF & EDDY | AECOM

Water  
Water Resources  
Wastewater  
Wet Weather  
Hazardous Waste  
General Engineering



New York Office  
605 Third Avenue, New York, NY 10158  
212.667.3076 Fax: 212.661.7535  
Corporate Headquarters  
701 Edgewater Drive, Wakefield, MA 01863  
781.246.5200 Fax: 781.245.6293  
www.m-e.aecom.com

# Gehring Pumps

*The Best Kept Secret in Upstate New York*  
Contact Gehring Pumps for all your Pump,  
Process, Mixer, Parts, and Service needs

### Pumps

Peerless  
KSB  
Crane Deming  
Barnes  
Crown  
BJM  
Monoflo  
Goulds

### Process

Infilco Degremont  
Franklin Miller  
Biocube  
EDI  
Olympus Tech.  
Continental  
Brawn  
Hi-Tech  
Golden Harvest  
Alfa Laval  
Philadelphia Mixers

Contact Jacob Scherer, P.E.  
7607 Commons Blvd., Victor, New York

Phone: 585-425-4288 Fax: 585-425-4139  
[WWW.GEHRINGPUMPS.COM](http://WWW.GEHRINGPUMPS.COM)

## The Answer to ALL Your Blower Needs!

- Complete Blower Packages
- Noise Attenuating Enclosures
- Custom Design & Fabrication
- Blower Parts & Accessories



Excelsior Blower Systems, Inc. is the Gardner Denver Authorized Distributor and Warranty Center for Sutorbilt, Duroflow, Cycloblower, Triflow and Heliflow models. As one of the nations largest blower package

manufacturers, we have the proven experience of thousands of installations throughout the country. Responsive design, sizing and specification capabilities are available to all engineers.

### Blower Service & Repair

- Sutorbilt
- Duroflow
- Hoffman
- Gardner Denver
- Aerzen
- Roots
- Lamson
- MD-Pneumatics
- Spencer
- Others



### Our factory trained technicians are available for:

- Removal and installation
- Onsite repairs
- Pick-up and delivery
- Preventive maintenance contracts



## Excelsior Blower Systems, Inc.

[www.excelsiorblower.com](http://www.excelsiorblower.com)

Contact: Dan Fulton ■ 24 Cokesbury Rd, Suite 10, Lebanon, NJ 08833 ■ Ph: 908-236-8245 ■ Fax: 908-236-8246 ■ [dan@excelsiorblower.com](mailto:dan@excelsiorblower.com)

continued from page 14

This may create an uncontrolled situation where a “developing emergency” is created, possibly causing the local municipality to take emergency action to protect the public. This could potentially expose the owner to legal and regulatory liability.

A **partial breach** of a dam, sometimes referred to as partial removal, can increase spillway capacity and can sometimes be done by modifying an existing undersized spillway. If the maximum impounded water volume is decreased, resulting in a reduced potential floodwave and associated downstream inundation area, the potential hazard to downstream properties may also be decreased. A partial breach project could be limited to lowering the primary spillway elevation to reduce the volume stored in the dam’s normal pool. The project could be expanded to include constructing a larger breach in the dam so that no water is impounded during normal flow, yet some structure remains. Portions of the hydrologic and hydraulic analyses can be conducted using computer modeling programs such as the Army Corps of Engineers’ HEC-RAS to determine and compare the pre-versus post-modification downstream impacts of a hypothetical dam failure. Lessening the impact of the hypothetical dam failure can sometimes result in a lower hazard classification. The analysis can provide conclusive data to substantiate it as well as modification of an existing emergency action plan or declaring an existing emergency action plan to be no longer necessary. The analysis results can also be used to support a reduction in the required spillway capacity, or an increase in the calculated stability factors of safety, due to reduced design loads.

Another approach is a **full breach** of a dam. What distinguishes this type of project from a partial breach is that no structure of the demolished dam significantly remains to affect the hydraulics in the former dam location. A full breach project would likely include

removal of the dam structure, down to the existing downstream streambed elevation, and excavating sediment in a controlled manner, proceeding in an upstream direction from the former dam location. The excavation would be done to create a stream reach with an engineered grade line and route that minimizes further erosion of sediment. For a full breach project, computer modeling programs can be used to evaluate the stream dynamics in the area of the dam, both upstream and downstream, to demonstrate the stability of the remaining streambed. The reconstructed streambed would be hydraulically similar to the existing upstream or downstream reaches.

In New York, an Article 15 Dam Safety Permit is required for partial or full breach of a dam. A Dam Safety Permit application needs to include the items listed in 6NYCRR Part 608 and additional information as deemed necessary by the DEC. For this type of project, the application should include the following:

- Completed Joint Application Form and Supplement D-1
- Construction Plan Set, including for example:
  - plan, section, and detail drawings sufficient to show the work
  - demolition plan
  - control of water plan, to demonstrate a dry breach approach
- Construction Specifications including, for example:
  - disposal of debris/materials
  - size and placement of rip-rap and other materials
- Engineering report including, for example:
  - downstream hazard assessment for the proposed configuration
  - pre- and post-modification hydrologic and hydraulic analyses with an assessment of the need to revise flood insurance rate maps
  - geotechnical investigation data and design
  - structural stability evaluation


## LANGE RELIABILITY

# FACED WITH A CHALLENGE?

**WE KNOW HOW DIFFICULT IT CAN BE TO SELECT THE PROPER EQUIPMENT FOR YOUR WATER AND WASTE WATER PROJECTS.**

The J. Andrew Lange, Inc. company is built on a reputation for customer service and engineering expertise. Our technical knowledge of the products we represent and our design and engineering capabilities mean we can offer you the best combination of products and process to solve your water and waste water problems.

Since 1968, we have provided customers with reliable products, engineering expertise and outstanding customer service. When you run into a water or waste water problem, call us and give us the opportunity to provide a solution. **Call us today!**



**J. Andrew Lange, Inc.**

6006 Drott Drive, Suite B, East Syracuse, NY 13057-2943  
PH: 315/437-2300 • FAX: 315/437-5935 • [www.jalangeinc.com](http://www.jalangeinc.com)

- Emergency Action Plan (EAP) for “C” and “B” Hazard dams, and
- Inspection and Maintenance Plan for “C” and “B” Hazard dams.

Some other considerations unique to partial and full breach projects, which may require engineering attention, include these:

- Limits of earthwork and remaining channel configuration
- Hydraulic properties of spillways functioning as fish passages
- Channel reconstruction or restoration so as not to leave a head cutting condition
- Updating or even closeout of existing EAPs, which are no longer applicable

Dam safety concerns and scope of review does not cover the full range of environmental issues. Some other issues that may need to be considered include:

- Not removing invasive species (i.e., Lamprey eel) barriers
- Sediment testing, characterization and disposal
- Stream health determination, downstream macro invertebrate monitoring and geomorphic assessment

The stakeholders involved with these and other environmental issues are identified by the DEC regional Division of Environmental Permits staff during the application process.

Guidance, including references for technical assistance and tools to help guide applicants through the dam removal process is planned to be released later in the year. The NYS Department of Transportation, the Thruway Authority/Canal Corps, the US Fish and Wildlife Service, numerous NGOs and the DEC are participating in this effort.

*Randall J. Passmann, PE, is an environmental engineer in the NYSDEC Dam Safety Section.*



**They're not thinking about clean water but we are.**

Count on ARCADIS to deliver forward-thinking, innovative water, wastewater and environmental engineering to protect, clean and restore our most valuable resource.

Albany  
Tel 518.452.7826  
Tel 518.452.7082

Massena  
Tel 315.764.2239

Melville  
Tel 631.249.7600

New Hyde Park  
Tel 516.328.0464

New York City  
Tel 212.594.1860  
Tel 212.682.9271

Rochester  
Tel 585.385.0090

Syracuse  
Tel 315.446.9120

[www.arcadis-us.com](http://www.arcadis-us.com)

Imagine the result




**You wouldn't want to use our mixers in this.**  
But...they're ideal for mixing your digesters.



- Our improved mixer designs include:
- Automatic pressurized bearing lubrication
  - Automatic self-centering system
  - Stronger mixer shafts and housings
  - Flow deflectors and turbulence suppressors
  - Simplified drive belt tensioning systems
  - Quick release stainless steel belt guards
  - Higher pressure draft tube heat exchangers
  - Reversible non-fouling propellers
  - Optional VFD drives

OTT's mechanical sludge mixer designs are the result of more than 20 years of design and field experience. Our heavy-duty draft tube mixers can mount on top of new or existing digester covers or they can be located around the outside perimeter of the digester.



Olympus Technologies, Inc.  
P.O. Box 2326  
Eugene, OR 97402

Contact us at: [info@oti.cc](mailto:info@oti.cc)  
541.689.5851 (ph)  
541.689.5818 (fax)  
or visit us at [www.oti.cc](http://www.oti.cc)



*"Quality Always" since 1979*

Represented in NY by: Gehring Pump, Inc. 585.425.4288 Victor, NY